

CONTROLLER ASSEMBLIES

WEATHERMATIC® SMARTLINE CONVENTIONAL SERIES CONTROLLER ASSEMBLY

The Imperial Controller Assembly (ICA) is built with the highest quality standards using UL Listed stainless steel enclosures to provide simple and efficient installations in the field. All Assemblies include a pre-installed controller(s), 120VAC receptacles, terminal boards for wiring and mounting instructions. The Imperial Assemblies wiring harness is wired through the rear giving it a clean look.

As pre-assembled and pre-wired for convenience, the installer is responsible for setting the enclosure base (or Mounting Pad), installing conduits, wiring the 120VAC electrical to the receptacle, and connecting the valve wires to the terminal board. Optional flow, rain, and other sensing devices may also be connected to the terminal board.

Mounting bases (#MP) are ideal way to further reduce installation time by eliminating the need to a pour concrete base. All Imperial Assemblies include a limited 5 year warranty.



SPECIFICATIONS


The Imperial Controller Assembly shall include a UL Listed stainless steel vandal resistant enclosure with a removable backboard, 120VAC outlet receptacle, and terminal wire board with Remote Receiver Connector (RRC).

The electrical junction box shall include an on/off power switch and duplex receptacle with ground fault interrupt circuit.

The terminal wiring board shall be pre-mounted and wired through the rear side of the backboard and shall include screw-less cage-type terminal block connections including up to two slots per terminal and may accept 12 or 14 gauge AWG wires. The terminal board shall also include a reset-able fuse and sensor bypass switch.

The terminal board(s) shall have a maximum of forty eight (48) valve station locations including additional terminals for up to four (4) common wires, master valve(s), two (2) rain sensor terminals, pump start, flow sensor, and two-wire communication cables.

STRONG BOX ENCLOSURE TYPES



FRONT ENTRY

SIDE BY SIDE

DOUBLE WIDE

METER CONTROLLER

LITE CONTROLLER

TOP ENTRY

MOUNTING PAD

WEATHERMATIC® SMARTLINE CONVENTIONAL SERIES CONTROLLER ASSEMBLY PART NUMBERING GUIDE

Imperial Controller Assembly Part Number

ICAX-WMX-XX+XX/Options

ICAX- Specify Strong Box Stainless Steel Enclosure Type

FRONT ENTRY

| | | |
|----|--------------------|-------------------|
| 1= | 18"W x 36"H x 12"D | SB18-SS PEDESTAL |
| 2= | 18"W x 36"H x 24"D | SB18D-SS PEDESTAL |
| 3= | 24"W x 36"H x 12"D | SB24-SS PEDESTAL |
| 4= | 24"W x 36"H x 24"D | SB24D-SS PEDESTAL |
| 8= | 36"W x 36"H x 12"D | SB36-SS PEDESTAL |

ELECTRIC METER/ CONTROLLER ENCLOSURE

| | | | |
|-----|----------------------------------|--------------------|----------------------|
| 5A= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (100/100 AMP – 1 PH) |
| 5C= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (100/200 AMP – 1 PH) |
| 5D= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (100/100 AMP – 3 PH) |
| 5E= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (200/200 AMP – 3 PH) |

TOP ENTRY ENCLOSURES

| | | |
|----|----------------------|------------------|
| 6= | 16"W x 38"H x 15.5"D | SB-16SS PEDESTAL |
| 7= | 24"W x 38"H x 17"D | SB-22SS PEDESTAL |

WALL MOUNT ENCLOSURES AND BACKBOARDS

| | | |
|-----|--------------------|-------------------------------|
| 10= | 16"W x 32"H | BACKBOARD – WALL MOUNT |
| 11= | 22"W x 32"H | BACKBOARD – WALL MOUNT |
| 16= | 18"W x 36"H x 12"D | SB-18SSW WALL MOUNT ENCLOSURE |
| 17= | 24"W x 36"H x 12"D | SB-24SSW WALL MOUNT ENCLOSURE |

LITE DUTY ENCLOSURES

| | | |
|-----|--------------------------------|--------------------------|
| 12= | 16.75"W x 30"H x 8.25"D | LD-16SW WALL MOUNT |
| 13= | 16.75"W x 30"H x 8.25"D | LD-16SSW PEDESTAL |
| 15= | 17 1/2"W x 34 1/2"H x 11 1/2"D | LD-16 TOP ENTRY PEDESTAL |

WMX-XX+XX /OPTIONS

| | |
|-----------------|---|
| WMX | CONTROLLER MANUFACTURER WM = WEATHERMATIC SL4800 Series |
| WMX | CONTROLLER TYPE/COMMUNICATION <u>1 = SmartLine (12-48)</u> <u>2 = SmartLine with Air Card (12-48)</u> <u>3 = SmartLine with Air Card + Flow Capable (12-48)</u> 4 = N/A 5 = SmartLine Decoder (16, 24, 48 &, 96) 6 = SmartLine Decoder with Air Card (16, 24, 48 & 96) 7 = SmartLine Decoder with Air Card + Flow Capable (16, 24, 48 & 96) |
| XX | CONTROLLER #1 STATION QUANTITY (24, & 40) |
| +XX | CONTROLLER #2 STATION QUANTITY (24, & 40) |
| /OPTIONS | SATELLITE OPTIONS (See Options Section for available options) |

CONTROLLER ASSEMBLIES

WEATHERMATIC® SMARTLINE DECODER SERIES CONTROLLER ASSEMBLY

The Imperial Controller Assembly (ICA) is built with the highest quality standards using UL Listed stainless steel enclosures to provide simple and efficient installations in the field. All Assemblies include a pre-installed controller(s), 120VAC receptacles, terminal boards for wiring and mounting instructions. The Imperial Assemblies wiring harness is wired through the rear giving it a clean look.

As pre-assembled and pre-wired for convenience, the installer is responsible for setting the enclosure base (or Mounting Pad), installing conduits, wiring the 120VAC electrical to the receptacle, and connecting the valve wires to the terminal board. Optional flow, rain, and other sensing devices may also be connected to the terminal board.

Mounting bases (#MP) are ideal way to further reduce installation time by eliminating the need to a pour concrete base. All Imperial Assemblies include a limited 5 year warranty.



SPECIFICATIONS


The Imperial Controller Assembly shall include a UL Listed stainless steel vandal resistant enclosure with a removable backboard, 120VAC outlet receptacle, and terminal wire board with Remote Receiver Connector (RRC).

The electrical junction box shall include an on/off power switch and duplex receptacle with ground fault interrupt circuit.

The terminal wiring board shall be pre-mounted and wired through the rear side of the backboard and shall include screw-less cage-type terminal block connections including up to two slots per terminal and may accept 12 or 14 gauge AWG wires. The terminal board shall also include a reset-able fuse and sensor bypass switch.

The terminal board(s) shall have a maximum of forty eight (48) valve station locations including additional terminals for up to four (4) common wires, master valve(s), two (2) rain sensor terminals, pump start, flow sensor, and two-wire communication cables.

STRONG BOX ENCLOSURE TYPES



FRONT ENTRY

SIDE BY SIDE

DOUBLE WIDE

METER CONTROLLER

LITE CONTROLLER

TOP ENTRY

MOUNTING PAD

WEATHERMATIC® SMARTLINE DECODER SERIES CONTROLLER ASSEMBLY PART NUMBERING GUIDE

Imperial Controller Assembly Part Number

ICAX-WMX-XX+XX/Options

ICAX- Specify Strong Box Stainless Steel Enclosure Type

FRONT ENTRY

| | | |
|----|--------------------|-------------------|
| 1= | 18"W x 36"H x 12"D | SB18-SS PEDESTAL |
| 2= | 18"W x 36"H x 24"D | SB18D-SS PEDESTAL |
| 3= | 24"W x 36"H x 12"D | SB24-SS PEDESTAL |
| 4= | 24"W x 36"H x 24"D | SB24D-SS PEDESTAL |
| 8= | 36"W x 36"H x 12"D | SB36-SS PEDESTAL |

ELECTRIC METER/ CONTROLLER ENCLOSURE

| | | | |
|-----|----------------------------------|--------------------|----------------------|
| 5A= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (100/100 AMP – 1 PH) |
| 5C= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (100/200 AMP – 1 PH) |
| 5D= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (100/100 AMP – 3 PH) |
| 5E= | 18"W x 52"H x 20"D + 18"W x 52"H | SB-1852SS PEDESTAL | (200/200 AMP – 3 PH) |

TOP ENTRY ENCLOSURES

| | | |
|----|----------------------|------------------|
| 6= | 16"W x 38"H x 15.5"D | SB-16SS PEDESTAL |
| 7= | 24"W x 38"H x 17"D | SB-22SS PEDESTAL |

WALL MOUNT ENCLOSURES AND BACKBOARDS

| | | |
|-----|--------------------|-------------------------------|
| 10= | 16"W x 32"H | BACKBOARD – WALL MOUNT |
| 11= | 22"W x 32"H | BACKBOARD – WALL MOUNT |
| 16= | 18"W x 36"H x 12"D | SB-18SSW WALL MOUNT ENCLOSURE |
| 17= | 24"W x 36"H x 12"D | SB-24SSW WALL MOUNT ENCLOSURE |

LITE DUTY ENCLOSURES

| | | |
|-----|--------------------------------|--------------------------|
| 12= | 16.75"W x 30"H x 8.25"D | LD-16SW WALL MOUNT |
| 13= | 16.75"W x 30"H x 8.25"D | LD-16SSW PEDESTAL |
| 15= | 17 1/2"W x 34 1/2"H x 11 1/2"D | LD-16 TOP ENTRY PEDESTAL |

WMX-XX+XX /OPTIONS

| | |
|-----------------|--|
| WMX | CONTROLLER MANUFACTURER WM = WEATHERMATIC SL1600 Series |
| WMX | CONTROLLER TYPE/COMMUNICATION 1 = SmartLine (12-48) 2 = SmartLine with Air Card (12-48) 3 = SmartLine with Air Card + Flow Capable (12-48) 4 = N/A 5 = SmartLine Decoder (16, 24, 48 &, 96) 6 = SmartLine Decoder with Air Card (16, 24, 48 & 96) 7 = SmartLine Decoder with Air Card + Flow Capable (16, 24, 48 & 96) |
| XX | CONTROLLER #1 STATION QUANTITY (16, 24, 48, & 96 Decoder) |
| +XX | CONTROLLER #2 STATION QUANTITY 16, 24, 48, & 96 Decoder) |
| /OPTIONS | SATELLITE OPTIONS (See Options Section for available options) |